

Optimizing Performance of the Defense Waste Processing Facility



Jean M. Ridley, P.E.
Liquid Waste System Integration
Waste Disposition Projects
Savannah River Operations Office



Purpose

Discuss the process improvements to the Defense Waste Processing Facility (DWPF) resulting in improved efficiencies and production.



DWPF Vitrification History

Objective:


Process (vitrify) high level waste from tank farms into a stable waste form ready for disposal in the Federal Repository

- Design started in 1977
- Construction began 1983
- Radioactive operations began March 1996
- Poured 2471 Canisters as of 3/06/08 – 9.5 million lbs of glass
- Currently processing Sludge Batch 4
- Two melters to-date
 - 1st – 1333 cans – replaced in 2004
 - 2nd – 1138 cans to date
 - 3rd – ready
 - 4th – under construction




Sludge Stored in a Waste Tank

- Insoluble solids contained in the waste
- Settles to the bottom of a tank
- 9 % of volume (3 million gallons)
- 51 % of radioactivity (200 million curies [Ci])



Hydrogen (generated from radiolysis) bubbles up through the sludge

DWPF Process Overview



Vitrification Process

- Sludge mixed with glass formers (frit)
- Sludge/frit slurry fed to melter
- Slurry resides in melter at 1150°C for about 65 hours to permit thorough melting and mixing
- Melter heats melt pool by passing an electric current through it, i.e., “Joule” heating
- Molten glass is drawn from the melter through the melter pour spout to fill a canister
- Pour spout directs the molten pour stream into a canister while a connecting bellows provides a leak-tight seal
- Empty canisters are placed on a pour turn-table and rotated beneath the melter pour spout for filling




Processing Improvements

- Increased HLW Loading of Glass and Optimization of Throughput – 6% increase
- Glass Pump
- Heated Bellows Liner – 5% increase in attainment
- Melter Siphon Detector – 2% increase in attainment
- Melter Feed Pump Software Logic Changes – 2% increase in attainment
- Steam Atomized Scrubber (SAS) Operation vs. Recycle Water – 3% increase
- Optimized Frit




Waste Loading- Melt Rate- Throughput



Heated Bellows Liner

- Reduced downtime for cleanouts
- Increased attainment 5%



Other Process Improvements

- Melter Siphon Detector – 2% increase
- Melter Feed Pump Software Logic Changes – 2% increase
- Steam Atomized Scrubber (SAS) Operation vs. Recycle Water – 3% increase
- Frit Adjustments – ensures melt rate/throughput is optimized with constituents of sludge



Potential Improvements

- Gas Chromatographs (GC) – installation 3/08
 - less downtime due to GC problems
- Sludge Adjustment and Receipt Tank (SRAT) Optimization
- Technology Improvements
- Continued Monitoring of Existing Parameters



Challenges

- Equipment Maintenance
- Spare Parts
 - Pumps
 - Precipitate Reactor Feed Tank (PRFT) Transfer Pump
 - Strip Effluent Feed Tank (SEFT) Transfer Pump
 - 512-S Transfer Pump
 - Agitators
 - Sludge Receipt and Adjustment Tank (SRAT),
 - Slurry Mix Evaporator (SME)
 - Coils - SME Coil
 - Tanks
 - SME Tank
 - Melter Feed Tank (MFT)
 - SRAT

